

GENERAL INFO.

TYPICAL SPECIFICATIONS

INSTALLATION DRAWINGS

3E. PRE-PACKAGED FIBERGLASS SYSTEMS

FIBERGLASS LIFT STATION TYPES:

C-CHANNEL GRINDER PACKAGE:

1½" and 2" Discharge Pumps - Factory Prewired

Simplex - EasyELECTRIC with Stealth Panel, UltraCAP₂, Stainless "C" Rail

Simplex - EasyELECTRIC with Junction Box, Stainless "C" Rail

Duplex - UltraGRIND with Junction Box, Stainless "C" Rail

1½" and 2" Discharge Pumps - Jobsite wired

Simplex - UltraGRIND with Junction Box, Stainless "C" Rail

Simplex - Non-Sparking with Stainless "C" Rail, Fiberglass Cover

Duplex - UltraGRIND with Junction Box, Stainless "C" Rail

Duplex - Non-Sparking with Stainless "C" Rail, Steel Cover

HARD PIPED STATION FOR SEWAGE EJECTORS, EFFLUENT PUMPS, AND GRINDERS:

1½", 2", 3" Discharge Pumps - Jobsite Wired

Simplex - Schedule 80 PVC Piping, Solid Fiberglass or Aluminum Hatch Cover options

PIPE RAIL STATION FOR SEWAGE EJECTORS, EFFLUENT PUMPS, AND GRINDERS:

1½", 2", 3" Discharge Pumps - Jobsite Wired

Simplex - 1PH and 3PH Panel Options, Stainless Steel Rail, Solid Fiberglass or Aluminum

Hatch Duplex - 1PH and 3PH Panel Options, Stainless Steel Rail, Solid Fiberglass, Aluminum or Steel Hatch