

NSF 61 / 372 - Split Case Pumps

Item No.	Name of Part	Standard / Optional for NSF 61 / 372 Listed Pump
1A	Lower Half Casing	Cast Iron (125#) / Ductile Iron (300#)
1B	Upper Half Casing	Cast Iron (125#) / Ductile Iron (300#)
2	Impeller	Lead Free & Zinc Free Aluminum Bronze
6	Shaft (Sleeveless) - Unbalanced	416SS / 316SS
6	Shaft (Sleeved) - Unbalanced	Steel / 416SS / 316SS
6	Shaft (Sleeved) - Balanced	416SS / 316SS
7	Casing Ring	Lead Free & Zinc Free Aluminum Bronze
8	Impeller Ring	Lead Free & Zinc Free Aluminum Bronze / 12% CR SS
13	Packing	NA
14	Shaft Sleeve - Packing	NA
14	Shaft Sleeve - Seal	416SS / 316SS
16	Bearing (Inboard)	Steel
17	Packing Box Gland	NA
17A	Seal Cap	Ductile Iron
18	Bearing (Outboard)	Steel
20	Shaft Sleeve Nut	Bronze
24A	Shaft Collar	416SS / 316SS
29	Lantern Ring	Bronze
31	Bearing Housing (Inboard)	Cast Iron
32	Impeller Key	316SS
33	Bearing Housing (Outboard)	Cast Iron
38	Shaft Sleeve Gasket	Vellumoid
40	Deflector	Neoprene
41	Bearing Cap (Inboard)	Cast Iron
43	Bearing Cap (Outboard)	Cast Iron
65	Mechanical Seal (Stationary)	Ceramic / Silicon Carbide
	Mechanical Seal (Rotating)	Carbon / Silicon Carbide
	Mechanical Seal Elastomers	Buna (FDA)
68	Seal Collar	416SS / 316SS
73	Casing Gasket - Suction Side	Lexide
73A	Casing Gasket - Discharge Side	Lexide
127	Seal Piping	Copper
192	Retaining Ring (Bearing)	Steel